

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 July 2003 (10.07.2003)

PCT

(10) International Publication Number
WO 03/055475 A1

(51) International Patent Classification⁷: **A61K 31/137**

(21) International Application Number: **PCT/IB02/00001**

(22) International Filing Date: **3 January 2002 (03.01.2002)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(71) Applicant (for all designated States except US): **LEK PHARMACEUTICAL AND CHEMICAL COMPANY D.D. [SL/SL]; Legal Affairs and Industrial Property, Industrial Property Department, Verovskova 57, 1526 Luubljana (SL).**

(72) Inventors; and

(75) Inventors/Applicants (for US only): **JANEZ, Kerc [SL/SL]; Trebinjska 7, 1000 Ljubljana (SL). VLASTA, Humar [SL/SL]; Godic 63, 1242 Stahovica (SL).**

(81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,**

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **CONTROLLED RELEASE PHARMACEUTICAL FORMULATION CONTAINING VENLAFAXINE**

(57) Abstract: A solid controlled release pharmaceutical formulation for once daily administration comprises a core comprising venlafaxine, polyvinylpyrrolidone, a low viscosity hydrophilic polymer and a high viscosity hydrophilic polymer, and a polymeric coating comprising a water high permeable polymer, and a water low permeable polymer. The invention further relates to a process for the preparation of a solid controlled release pharmaceutical formulation comprising the steps of dissolving venlafaxine and polyvinylpyrrolidone in an organic solvent, applying the resulting solution onto low viscosity polymer, homogeneously mixing the obtained granulate with a high viscosity polymer, and compressing the granulate to obtain a core which is then coated with a polymeric coating comprising a water high permeable polymer and a water low permeable polymer.

CONTROLLED RELEASE PHARMACEUTICAL FORMULATION CONTAINING
VENLAFAXINE

This invention relates to a controlled release pharmaceutical formulation for once daily administration, in particular to a controlled release pharmaceutical formulation of venlafaxine.

Venlafaxine, chemically named (\pm) 1-[2-(dimethylamino)-1-(4-methoxyphenyl)ethyl]-cyclohexanol, is an antidepressant disclosed in EP-A-0 112 669. Presently venlafaxine hydrochloride is administered to adults as conventional immediate release tablets or as 24 hour extended-release multiparticulate capsules.

Venlafaxine hydrochloride is very soluble in water. It is known that it is very difficult to develop a pharmaceutical form with a very slow dissolution rate of freely soluble drug. Besides that, venlafaxine hydrochloride is polymorphic, so dissolution is dependent also on polymorphic form and particle size of particular polymorphic form. Therefore, it is a special task to develop such a pharmaceutical formulation that would sustain and control the dissolution of freely soluble drug over 24 hour period.

EP-A-0 797 991 and WO 99/22724 disclose encapsulated venlafaxine extended release dosage formulation of venlafaxine hydrochloride, which provides in a single dose, a therapeutic blood serum level over a twenty four hour period. Gelatine capsules are filled with film coated spheroids containing venlafaxine hydrochloride. EP-A-0 797 991 states that numerous attempts to produce extended release tablets by hydrogel technology proved to be fruitless because the compressed tablets were either physically unstable (poor compressibility or capping problems) or dissolved too rapidly in dissolution studies. Typically, the tablets prepared as hydrogel sustained release formulations gave 40-50% dissolution at 2 hours, 60-70%

dissolution at 4 hours and 85-100% dissolution at 8 hours (EP-A-0 797 991).

WO 94/27589 and WO 01/37815 describe osmotic dosage forms containing venlafaxine hydrochloride.

The object of the invention is to provide an improved solid controlled release pharmaceutical formulation containing venlafaxine and a process for the preparation thereof. This object is achieved for example by the combination of the features in each of the independent claims 1 and 26. Preferable embodiments of the invention are defined in the dependent claims.

The pharmaceutical formulation of the present invention comprises for example a core consisting of an active drug which may be advantageously in amorphous form, polyvinylpyrrolidone, a combination of two hydrophilic polymers having different viscosities and optionally other commonly used ingredients for solid dosage forms. The core is coated with a polymeric coating comprising a combination of two polymers having different water permeabilities. A plasticizer and other commonly used ingredients for film coating may be optionally added thereto.

A solid controlled release formulation according to a preferred embodiment of the present invention comprises for example a core consisting of venlafaxine, polyvinylpyrrolidone, a combination of two different hydrophilic polymers preferably from the group of cellulose ethers from which the first one may be a low viscosity cellulose ether and the second one may be a high viscosity cellulose ether, and other commonly used ingredients for solid dosage forms. The core is coated with a polymeric coating comprising a combination of two different polymers from which the first one is water high permeable polymer and the second one is water low permeable polymer. It is advantageous to further add a plasticizer and other commonly used ingredients for film coating.

Venlafaxine may be in a form of a pharmaceutically acceptable salt, preferably in a form of venlafaxine hydrochloride.

It was unexpected that once daily formulation of venlafaxine hydrochloride could be obtained using hydrogel technology based on a combination of low and high viscosity hydrophilic polymers although the active substance is extremely hydrophilic and water soluble.

Controlled release of venlafaxine hydrochloride over 24 hours is achieved by a combination of two hydrophilic polymers of different viscosity in the core and of two polymers of different water permeability in the coating.

The active ingredient stabilised with polymers is dispersed at the molecular level and has therefore always the same particle size and the same specific surface area. Consequently, the dissolution rate is not polymorph dependent but dependent solely on the combination and ratio of low and high viscosity hydrophilic polymers in the core and on combination and ratio of water high permeable and water low permeable polymers in the coating.

The water soluble polymer polyvinylpyrrolidone prevents the crystallisation of the active ingredient, simultaneously it is a carrier of the active ingredient in the coprecipitate. Polyvinylpyrrolidone with a K-value (relative viscosity of the compound in water solution with regard to water) preferably ranging from 10 to 95, more preferably in the range from 24 to 32, with an average molecular weight preferably ranging from 2000 g/mol to 110000g/mol, more preferably in the range from 25000 g/mol to 50000 g/mol may be used. Polyvinylpyrrolidone is preferably present in the formulation in the range from 5 to 40 wt%, more preferably from 10 to 20 wt%, with respect to the total weight of the formulation.

The low viscosity hydrophilic polymer acts as a carrier of the active ingredient which simultaneously inhibits its crystallisation in the coprecipitate of venlafaxine hydrochloride and polyvinylpyrrolidone, and together with other ingredients it modifies the release of the active substance in such a way that it is sustained over 24 hour period. The low viscosity hydrophilic polymer may preferably be present in a quantity from 10 to 70 wt%, more preferably from 20 to 50 wt%, with respect to the total weight of the pharmaceutical formulation.

For providing a stable, preferably amorphous form of the active ingredient in the novel pharmaceutical formulation the required weight ratio between the water soluble polymer polyvinylpyrrolidone and the low viscosity hydrophilic polymer is preferably in the range from 10:1 to 1:10, more preferably in the range from 1:3 to 3:1.

The combination of the carriers i.e. the water soluble polymer polyvinylpyrrolidone and the low viscosity hydrophilic polymer has a double effect and the advantage that it stabilises the amorphous form of the active ingredient and simultaneously modifies the release of the amorphous active ingredient in such a way that it is sustained, repeatable and independent of the amorphous or polymorphous form of the active ingredient, its particle size and specific surface area.

The high viscosity hydrophilic polymer in combination with low viscosity hydrophilic polymer modifies the release of the active substance in such a way that it is sustained over 24 hour period.

High viscosity hydrophilic polymer is present preferably in a quantity from 5 to 70 wt%, more preferably from 7 to 50 wt%, with respect to the total weight of the pharmaceutical formulation.

A low viscosity and a high viscosity hydrophilic polymer can preferably be selected from cellulose ethers selected from the group consisting of methylcellulose, ethylcellulose, hydroxyethylcellulose, propylcellulose, hydroxypropylcellulose, hydroxypropylmethylcellulose, carboxymethylcellulose, preferably hydroxyethylcellulose, hydroxypropylcellulose and hydroxymethylpropylcellulose. Combinations may also be used.

Particularly preferable cellulose ether is hydroxypropylmethylcellulose. A low viscosity hydroxypropylmethylcellulose is defined as one having preferably a molecular weight of 55,000 or less and viscosity of 800 mPas or less. A high viscosity hydroxypropylmethylcellulose is defined as one preferably having a molecular weight of 60,000 or greater and viscosity of 1000 mPas or greater. Different types of hydroxypropylmethylcellulose may be used.

	% methoxyl	% hydroxy-propoxyl	Relative rate of hydration	Viscosity mPas
Type K	19-24	7-12	fastest	3, 100, 4000, 15000, 10000
Type E	28-30	7-12	next fastest	3, 5, 6, 15, 50, 4000
Type F	27-30	4-7, 5	slower	50, 4000

For providing a sustained release of highly soluble amorphous active ingredient from a novel pharmaceutical formulation over 24 hour period the required ratio between the low viscosity and high viscosity hydrophilic polymer is preferably from 10:1 to 1:3, more preferably from 6:1 to 1:2, in particular preferably from 3:1 to 1:1.

The core may also contain other usual ingredients useful in the preparation of solid pharmaceutical forms such as fillers, binders, swelling excipients, glidants, lubricants etc.

The core may contain one or more fillers such as lactose, starch, saccharose, glucose, microcrystalline cellulose, mannitol, sorbitol, calcium hydrogen phosphate, aluminium silicate, sodium chloride. Further it may contain one or more binders such as starch, gelatine, carboxymethylcellulose, polyvinylpyrrolidone, crosslinked polyvinylpyrrolidone, sodium alginate, microcrystalline cellulose etc.; one or more disintegrants such as starch, cross-linked sodium carboxymethylcellulose, cross-linked polyvinylpyrrolidone, sodium starch glycolate etc., one or more glidants such as magnesium stearate, calcium stearate, aluminium stearate, stearic acid, palmitic acid, cetanol, stearyl, polyethylene glycols of various molecular weights, talc, etc., one or more lubricants such as stearic acid, calcium, magnesium or aluminium stearate, siliconized talc etc.

The formulation contains in a preferred embodiment from 10 to 400 mg of venlafaxine, more preferably from 30 to 200 mg of venlafaxine, particularly preferably from 37,5 to 150 mg of venlafaxine. venlafaxine is in a form of pharmaceutically acceptable salt, more preferably as venlafaxine hydrochloride.

The film coating comprises a combination of two different polymers from which the first one is a water high permeable polymer and the second one is a water low permeable polymer.

As a water high permeable polymers are considered polymers which are soluble (suitably 3.3% or more, more suitably 5% or more, even more suitably 10% or more, particularly suitably 50% or more and especially suitably 70% or more) in water (e.g. hydroxypropylcellulose, hydroxypropylmethylcellulose, methylcellulose and hydroxyethylcellulose) or can achieve water permeability by swelling or salt formation (e.g. methacrylate aminoester copolymer, methylcellulose) or contain groups

permeable for water in a high proportion (suitably molar ratio of water permeable to water non-permeable groups is 1:30 or more) (e.g. high permeable poly(ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride).

As water low permeable polymers are considered polymers which are insoluble in water, some in entire physiological pH (e.g. ethylcellulose) and some in acidic pH (e.g. cellulose acetate phthalate, methacrylic acid copolymers, polyvinyl acetate phthalate, cellulose acetate trimellitate, hydroxypropylmethylcellulose phthalate), or contain groups permeable for water in a small proportion (suitably molar ratio of water permeable to water non-permeable groups is 1:30 or less) (e.g. low permeable poly (ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride)..

Water high permeable polymer may preferably be selected from methylcellulose, hydroxypropylcellulose, hydroxypropylmethylcellulose, hydroxyethylcellulose, methacrylate aminoester copolymer, high permeable poly (ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride, preferably hydroxypropylcellulose, hydroxypropylmethylcellulose, methylcellulose and high permeable poly (ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride, most preferably from hydroxypropylcellulose, hydroxypropylmethylcellulose and high permeable poly (ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride. The selection of the water high permeable polymer should not be restricted by these examples.

Water low permeable polymer may preferably be selected from ethylcellulose, cellulose acetate phthalate, methacrylic acid copolymers, polyvinyl acetate phthalate, cellulose acetate

trimellitate, hydroxypropylmethylcellulose phthalate and low permeable poly (ethylacrylate, methylmethacrylate) .
trimethylammoniummethylmethacrylate chloride, preferably ethylcellulose, hydroxypropylmethylcellulose phthalate, polyvinyl acetate phthalate and low permeable poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride, most preferably from ethylcellulose, hydroxypropylmethylcellulose phthalate and low permeable poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride. The selection of the water low permeable polymer should not be restricted by these examples.

The combinations of water high permeable and water low permeable polymers may be selected in particular from, but not limited to, combination of hydroxypropylmethylcellulose and hydroxypropylmethylcellulose phthalate, hydroxypropylcellulose and hydroxypropylmethylcellulose phthalate, hydroxypropylmethylcellulose and ethylcellulose, hydroxypropylcellulose and ethylcellulose, hydroxypropylmethylcellulose and polyvinyl acetate phthalate, hydroxypropylcellulose and polyvinyl acetate phthalate, high permeable poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride and low permeable poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride, preferably hydroxypropylmethylcellulose and hydroxypropylmethylcellulose phthalate, hydroxypropylcellulose and ethylcellulose, hydroxypropylmethylcellulose and ethylcellulose, high permeable poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride and low permeable poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride.

The ratio between the water high permeable and water low permeable polymers is preferably from 10:1 to 1:5, more

preferably from 6:1 to 1:4, particularly preferably from 3:1 to 1:3.

The coating is preferably present in the formulation in the range from 1 to 15 wt%, more preferably from 2 to 10 wt%, with respect to the total weight of the formulation.

The coating may also contain other usual ingredients useful in the preparation of film coated solid dosage forms such as plasticizers, fillers, antisticking agents, antifoams, colorants etc.

The coating may contain one or more plasticizers such as acetyl tributyl citrate, acetyl triethyl citrate, acetylated fatty acid glycerides, castor oil, dibutyl phthalate, diethyl phthalate, diethyl sebacate, dibutyl sebacate, dimethyl phthalate, glycerol, glycerol monostearate, glyceryl triacetate, polyethylene glycols, polyoxyethylene/polyoxypropylene copolymers, propylene glycol, tributyl citrate, triethyl citrate. Further it may contain one or more fillers such as lactose, polydextrose and maltodextrin; one or more antisticking agents such as talc, magnesium stearate, calcium stearate, etc., one or more antifoams such as dimethylpolysiloxane, etc., one or more colorants such as titanium dioxide, iron oxides, lakes, etc.

A combination of amorphous form of an active ingredient in the coprecipitate with water soluble polyvinylpyrrolidone and a combination of low viscosity and high viscosity hydrophilic polymer in the core and a combination of water high permeable and water low permeable polymer in the coating, prepared in a certain ratio between the single components of the formulation according to the process of the invention, which is simple and technologically as well as economically acceptable, has hitherto not been described in the literature. The granulation of an active ingredient, the water soluble polymer polyvinylpyrrolidone and a combination of low viscosity and high viscosity hydrophilic polymer and other ingredients

suitable for preparation of solid pharmaceutical forms has good compressibility, so prepared tablets are firm, have low friability and together with a combination of water high permeable and water low permeable polymer in the coating make possible a sustained release of the amorphous active ingredient from pharmaceutical formulation over 24 hour period. Due to the preferable amorphous form of the active ingredient, the release rate of the active ingredient is not dependent on polymorphic form and particle size of active ingredient but solely on the combination and ratio of low and high viscosity hydrophilic polymers in the core and on combination and ratio of water high permeable and water low permeable polymer in the coating.

The above object can also be achieved by a process defined in Claim 26. For example in the first step of the preparation of a pharmaceutical formulation according to the invention an active ingredient and the water soluble polymer polyvinylpyrrolidone are dissolved in an organic solvent at a temperature e.g. from 20 to 60°C, and preferably in a fluid bed granulator. The obtained solution is applied, preferably sprayed onto a low viscosity hydrophilic polymer such as e.g. cellulose ether in the fluid bed. As the active ingredient there can be used an amorphous form or a polymorphous form of the active ingredient which in the process of coprecipitation according to the invention is converted into an amorphous form stabilised with water soluble polyvinylpyrrolidone and low viscosity hydrophilic polymer. Organic solvents useful for this purpose can be selected from group of alcohols, ketones, esters, aliphatic hydrocarbons, halogenated hydrocarbons, cycloaliphatic, aromatic, heterocyclic solvents or mixtures thereof. Typical solvents can be ethanol, methanol, isopropyl alcohol, n-butyl alcohol, acetone, diethyl ether, ethyl acetate, isopropyl acetate, methyl acetate, dichloromethane, chloroform, mixtures of these solvents such as ethanol and acetone, methanol and acetone, dichloromethane and methanol and mixtures thereof. If a polymorphous form of the active ingredient is chosen, it is in the process of the invention

converted into an amorphous form which is stabilised with water soluble polymer polyvinylpyrrolidone and low viscosity hydrophilic polymer. The obtained granulation is suitably regranulated through a sieve of mesh size 0.5 mm at room temperature.

The second step of the preparation of a pharmaceutical formulation according to the invention is, for example, conducted in such a manner that at room temperature the granulation obtained in the first step is homogeneously blended with a high viscosity hydrophilic polymer and other usual adjuvants useful in the preparation of solid pharmaceutical forms such as lactose, polyvinylpyrrolidone, cross-linked polyvinylpyrrolidone, starch, calcium hydrogen phosphate, calcium hydrogen carbonate, aluminium silicate, magnesium stearate, talc, or generally with fillers, binders, disintegrants, glidants, lubricants etc.

The components are compressed to obtain a core which may suitably be provided as tablets obtainable with known tableting machines. Thus it is possible to prepare tablets with controlled release of an amorphous active ingredient in a relatively simple and economical way.

In the third step of preparation of a pharmaceutical formulation according to the invention the obtained cores are, for example, film coated with a combination of water high permeable and water low permeable polymer.

The coating can be performed using dispersion or colloidal solution. Colloidal solution is prepared by dissolving the polymers e.g. in an organic solvent, in mixtures of organic solvents or in mixtures thereof with water. As organic solvent ethanol, methanol, propan-2-ol, acetone, ethyl acetate, glacial acetic acid, glycols, dichloromethane, dimethyl formamide, dimethylsulfoxide, dioxane chloroform, toluene, methylene chloride, benzene, diaceton alcohol, ethoxyethyl acetate, ethylene glycol monoacetate, ethyl lactate, methoxyethyl

acetate, β -methoxyethylene alcohol, methylethyl ketone can be used.

Coating dispersion can be prepared either by mixing powders of polymers or other suitable ingredients in organic solvent or in combination of organic solvent with water or by mixing and diluting aqueous dispersion of polymers with water.

In the second step plasticizer or a mixture of plasticizers may be optionally added to the polymer colloidal solution or dispersion of polymers and then the suspension of colorants, antisticking agents, fillers, antifoams may be added.

The coating can be performed by means of known coating techniques in perforated coating pans. Thus it is possible to prepare film coated tablets with sustained release of an amorphous active ingredient in a relatively simple and economical way.

The invention is illustrated, but in no way limited by the following examples:

Example 1

Composition of one tablet

Core:

Venlafaxine hydrochloride	150mg
Polyvinylpyrrolidone K30	150mg
Hydroxypropylmethylcellulose Methocel F50P	450mg
Hydroxypropylmethylcellulose Methocel K100MP	70mg
Ludipress	173mg
Talc	5mg
Mg stearate	2mg

Coating:

Hydroxypropylmethylcellulose Pharmacoat 606	22,695mg
Hydroxypropylmethylcellulose phthalate	9,726mg

Triethyl citrate	2,598mg
Iron oxide yellow	0,788mg
Titanium dioxide	2,373mg
Talc	0,324mg

A batch of 800 tablets was prepared according to the following procedure:

Crystalline venlafaxine hydrochloride (120 g) and polyvinylpyrrolidone K30 (120 g) (Kollidon 30, BASF; Plasdone K-30, ISP GAF) were dissolved in ethanol (960 g) under intensive stirring at room temperature. The formed solution (1200 g) was in a fluid bed at an inlet air temperature from 70°C to 85°C sprayed onto hydroxypropylmethylcellulose (360 g) with a viscosity of 50 mPas (Methocel F50 premium, Dow Chemicals) and with an average molecular weight of 19000 g/mol. The so prepared granulation (600 g) was dried in a fluid bed and regranulated through a sieve with mesh size 0.5 mm. To the granulation there were added hydroxypropylmethylcellulose (56 g) with a viscosity of 100000 mPas (Methocel K100M premium, Dow Chemicals) and with an average molecular weight of 215000 g/mol, Ludipress (138,4 g) (93,4 wt% of lactose monohydrate + 3,2 wt% of polyvinylpyrrolidone K30 (Kollidon 30) + 3,4 wt% of cross-linked polyvinylpyrrolidone (Kollidon CL, BASF Germany)), talc (4 g) and magnesium stearate (1,6 g) and they were homogeneously blended at room temperature. The so prepared granulation with amorphous venlafaxine hydrochloride was compressed into tablets using usual tableting machine so that tablets with a weight of 950 mg were obtained.

Hydroxypropylmethylcellulose (36,312 g) (Pharmacoat 606, Shin Etsu Chemical Co. Japan) with a viscosity of 6 mPas , Hydroxypropylmethylcellulose phthalate (15,562 g) (HP-50, Shin Etsu Chemical Co. Japan) and triethyl citrate (4,150 g) (Morflex) were dissolved while stirring in a mixture of ethanol (410,774 g) and water (153,742 g), and then homogenised (Ultraturax, 30 min.) suspension of titanium dioxide (3,797 g),

iron oxide yellow (1,261 g) (Sicopharm 10, BASF) and talcum (0,518 g) in water (22,304 g) was added. Prepared suspension was sprayed onto cores so that the film coating in a weight ratio of about 4,8 wt.% regard to core was obtained. Tablets were also polished with talcum (0,563 g).

Dissolution of the tablets.

Apparatus: apparatus 2 (USP 23), 100 rpm
Medium: 0-2 hours: artificial gastric juice pH 1.2
 2-24 hours: artificial intestinal juice pH 6.8
Temperature: 37°C
Quantitative analysis: UV spectrophotometry, 273 nm

Table 1: Percentage of released venlafaxine vs. dissolution time

Dissolution time (h)	Percentage of released venlafaxine
1	13,2
2	22,0
3	32,1
4	39,6
6	51,3
8	60,7
10	68,5
12	74,9
14	80,3
16	84,6
18	88,2
20	91,9
22	93,4
24	95,5

From the above table it is evident that venlafaxine dissolution is sustained over 24 hour period.

Example 2

Composition of one tablet

Core:

Venlafaxine hydrochloride	169,73 mg
Polyvinylpyrrolidone K30	150 mg
Hydroxypropylmethylcellulose Methocel F50P	380,27 mg
Hydroxypropylmethylcellulose Methocel K100MP	150 mg
Ludipress	93 mg
Talc	5 mg
Mg stearate	2 mg

Coating:

Hydroxypropylcellulose Klucel EF	7,620 mg
Ethylcellulose N7	17,780 mg
Triethyl citrate	2,298 mg
Titanium dioxide	7,756 mg
Talc	2,546 mg

A batch of 800 tablets was prepared according to the following procedure: Tablet cores were prepared according to the same procedure as in Example 1.

Hydroxypropylcellulose (12,192 g) (Klucel EF, Hercules, Wilmington) with an average molecular weight of 60000 g/mol and a viscosity of 5 - 10 mPas, Ethylcellulose (28,448 g) (N7, Hercules, Wilmington) ethoxyl content 48,0 - 49,5% and viscosity 5,6 - 8 mPas and triethyl citrate (3,677 g) (Morflex) were dissolved while stirring in ethanol (548,823 g), and then homogenised (Ultraturax, 30 min.) suspension of titanium dioxide (12,410 g) and talcum (4,073 g) in ethanol (65,932 g) was added. Prepared suspension was sprayed onto cores so that the film coating in a weight ratio of about 4,0 wt.% regard to the core was obtained. Tablets were also polished with talcum (0,563 g).

Dissolution of the tablets.

Apparatus: apparatus 2 (USP 23), 150 rpm
Medium: 0-2 hours: artificial gastric juice pH 1.2
2-24 hours: artificial intestinal juice pH 6.8
Temperature: 37°C
Quantitative analysis: UV spectrophotometry, 273 nm

Table 1: Percentage of released venlafaxine vs. dissolution time

Dissolution time (h)	Percentage of released venlafaxine
0,5	1,0
1	4,4
1,5	8,4
2	12,4
3	21,1
4	28,0
6	40,0
8	50,1
10	58,8
12	66,6
16	78,8
18	83,3
20	87,1
24	92,0

From the above table it is evident that venlafaxine dissolution is sustained over 24 hour period.

Example 3

Composition of one tablet

Core:

Venlafaxine hydrochloride	169,73 mg
Polyvinylpyrrolidone K30	150 mg
Hydroxypropylmethylcellulose Methocel F50P	380,27 mg
Hydroxypropylmethylcellulose Methocel K100MP	150 mg
Ludipress	93 mg
Talc	5 mg
Mg stearate	2 mg

Coating:

Hydroxypropylcellulose Klucel EF	10,160 mg
Ethylcellulose N7	15,240 mg
Triethyl citrate	2,298 mg
Titanium dioxide	7,756 mg
Talc	2,546 mg

A batch of 800 tablets was prepared according to the following procedure: Tablet cores were prepared according to the same procedure as in Example 1.

The coating of the tablet cores was performed according to the same procedure as an example 2 only a ratio of Hydroxypropylcellulose to Ethylcellulose 1:1,5 was used.

Dissolution of the tablets.

Apparatus:	apparatus 2 (USP 23), 150 rpm
Medium: 0-2 hours:	artificial gastric juice pH 1.2
2-24 hours:	artificial intestinal juice pH 6.8
Temperature:	37°C
Quantitative analysis:	UV spectrophotometry, 273 nm

Table 1: Percentage of released venlafaxine vs. dissolution time

Dissolution time (h)	Percentage of released venlafaxine
0,5	5,8
1	11,8
1,5	16,9
2	21,1
3	29,9
4	37,0
6	48,8
8	58,7
10	67,0
12	74,2
16	84,7
18	88,2
20	91,0
24	94,1

Example 4

Composition of one tablet

Core:

Venlafaxine hydrochloride	169,73 mg
Polyvinylpyrrolidone K30	150 mg
Hydroxypropylmethylcellulose Methocel F50P	380,27 mg
Hydroxypropylmethylcellulose Methocel K100MP	250 mg
Ludipress	93 mg
Talc	5 mg
Mg stearate	2 mg

Coating:

Eudragit RL30D	2,450 mg
Eudragit RS30D	1,050 mg
Triethyl citrate	0,700 mg
Titanium dioxide	3,815 mg
Talc	5,404 mg
Polyethylene glycol 6000	0,318 mg
Polydimethylsiloxane	0,032 mg

A batch of 800 tablets was prepared according to the following procedure: Tablet cores were prepared according to the same procedure as in Example 1.

The coating of the tablet cores was performed according to the following procedure:

In the first step, polyethylene glycol (2,289 g) with a molecular weight of 5400-6600 (Clariant) was dissolved in part of the water (4,647 g). This solution and talcum (38,910 g), titanium dioxide (27,468 g), dimethylpolysiloxane (0,231 g) (Merck) were then stirred into part of the water (155,577 g) and homogenised (Ultraturrax, 30 min.). To eliminate air bubbles stirring of pigment suspension was continued overnight (approx. 12 hours).

The polymer dispersion were prepared from Eudragit RL 30D (58,800 g 30% aqueous dispersion of poly (ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride), Eudragit RS 30D (25,200 g 30% aqueous dispersion of poly (ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride), triethyl citrate (5,040 g) and water (139,620 g) while mixing for 30 min.. The pigment suspension and polymer dispersion were mixed for 20 min shortly before use.

So prepared suspension was sprayed onto cores so that the film coating in a weight ratio of about 1,3 wt.% regard to the core was obtained.

Dissolution of the tablets.

Apparatus: apparatus 2 (USP 23), 150 rpm
Medium: 0-2 hours: artificial gastric juice pH 1.2
2-24 hours: artificial intestinal juice pH 6.8
Temperature: 37°C
Quantitative analysis: UV spectrophotometry, 273 nm

Table 1: Percentage of released venlafaxine vs. dissolution time

Dissolution time (h)	Percentage of released venlafaxine
0,5	10,0
1	15,0
1,5	19,4
2	23,1
3	31,2
4	37,5
6	48,1
8	56,8
10	64,2
12	70,0
16	81,2
18	85,1
20	88,2
24	92,7

From the above table it is evident that venlafaxine dissolution is sustained over 24 hour period.

Example 5

Composition of one tablet

Core:

Venlafaxine hydrochloride	169,73 mg
Polyvinylpyrrolidone K30	150 mg
Hydroxypropylmethylcellulose Methocel F50P	380,27 mg
Hydroxypropylmethylcellulose Methocel K100MP	250 mg
Ludipress	93 mg
Talc	5 mg
Mg stearate	2 mg

Coating:

Hydroxypropylcellulose Klucel EF	12,700 mg
Ethylcellulose N7	12,700 mg
Triethyl citrate	2,298 mg
Titanium dioxide	7,756 mg
Talc	2,546 mg

A batch of 800 tablets was prepared according to the following procedure: Tablet cores were prepared according to the same procedure as in Example 1.

The coating of the tablet cores was performed according to the same procedure as an example 2 only a ratio of hydroxypropylcellulose to ethylcellulose 1:1 was used.

Dissolution of the tablets.

Apparatus:	apparatus 2 (USP 23), 150 rpm
Medium: 0-2 hours:	artificial gastric juice pH 1.2
2-24 hours:	artificial intestinal juice pH 6.8
Temperature:	37°C
Quantitative analysis:	UV spectrophotometry, 273 nm

Table 1: Percentage of released venlafaxine vs. dissolution time

Dissolution time (h)	Percentage of released venlafaxine
0,5	8,2
1	13,5
1,5	18,1
2	22,0
3	30,6
4	37,3
6	48,5
8	57,9
10	65,7
12	72,6
16	83,3
18	87,3
20	90,4
24	94,2

From the above table it is evident that venlafaxine dissolution is sustained over 24 hour period.

Claims:

1. A solid controlled release pharmaceutical formulation for once daily administration comprising
a core comprising venlafaxine, polyvinylpyrrolidone, a low viscosity hydrophilic polymer and a high viscosity hydrophilic polymer; and
a polymeric coating comprising a water high permeable polymer, and a water low permeable polymer.
2. The formulation of claim 1 wherein venlafaxine is in a form of venlafaxine hydrochloride.
3. The formulation of claim 1 and 2 wherein venlafaxine is in amorphous form.
4. The formulation of claim 1 wherein the amount of venlafaxine is from 10 to 400 mg.
5. The formulation of claim 1 wherein the amount of venlafaxine is from 37,5 to 150 mg.
6. The formulation of claim 1 wherein the amount of venlafaxine is 75 mg.
7. The formulation of claim 1 wherein the amount of venlafaxine is 150 mg.
8. The formulation of claim 1 wherein the low viscosity hydrophilic polymer and the high viscosity hydrophilic polymer in the core are selected from cellulose ethers.
9. The formulation of claim 1 wherein the low viscosity hydrophilic polymer and the high viscosity hydrophilic polymer in the core are selected from the group consisting of methylcellulose, ethylcellulose, hydroxyethylcellulose,

propylcellulose, hydroxypropylcellulose, hydroxypropylmethylcellulose or carboxymethylcellulose.

10. The formulation of claim 1 wherein the low viscosity hydrophilic polymer and the high viscosity hydrophilic polymer in the core are a low viscosity hydroxypropylmethylcellulose and a high viscosity hydroxypropylmethylcellulose.

11. The formulation of claim 1 wherein the ratio between polyvinylpyrrolidone and the low viscosity hydrophilic polymer in the core is from 10:1 to 1:10.

12. The formulation of claim 1 wherein the ratio between polyvinylpyrrolidone and the low viscosity hydrophilic polymer in the core is from 1:3 to 3:1.

13. The formulation of claim 1 wherein the ratio between the low viscosity hydrophilic polymer and the high viscosity hydrophilic polymer in the core is from 10:1 to 1:3.

14. The formulation of claim 1 wherein the ratio between the low viscosity hydrophilic polymer and the high viscosity hydrophilic polymer in the core is from 3:1 to 1:1

15. The formulation of claim 1 wherein the water high permeable polymer in the coating is selected from the group consisting of methylcellulose, hydroxypropylcellulose, hydroxypropylmethylcellulose, hydroxyethylcellulose, methacrylate aminoester copolymer, high permeable poly (ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride.

16. The formulation of claim 1 wherein the water high permeable polymer in the coating is selected from the group consisting of hydroxypropylcellulose, hydroxypropylmethylcellulose and high permeable poly

(ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride.

17. The formulation of claim 1 wherein the water low permeable polymer in the coating is selected from ethylcellulose, cellulose acetate phthalate, methacrylic acid copolymers, polyvinyl acetate phthalate, cellulose acetate trimellitate, hydroxypropylmethylcellulose phthalate and low permeable poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride.

18. The formulation of claim 1 wherein the water low permeable polymer in the coating is selected from ethylcellulose, hydroxypropylmethylcellulose phthalate and low permeable poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride.

19. The formulation of claim 1 wherein the combinations of water high permeable and water low permeable polymers is selected from: hydroxypropylmethylcellulose and hydroxypropylmethylcellulose phthalate, hydroxypropylcellulose and hydroxypropylmethylcellulose phthalate, hydroxypropylmethylcellulose and ethylcellulose, hydroxypropylcellulose and ethylcellulose, hydroxypropylmethylcellulose and polyvinyl acetate phthalate, hydroxypropylcellulose and polyvinyl acetate phthalate, high permeable poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride and low permeable poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride.

20. The formulation of claim 1 wherein the combination of water high permeable and water low permeable polymers is selected from the following combinations:
hydroxypropylmethylcellulose and hydroxypropylmethylcellulose phthalate, hydroxypropylcellulose and ethylcellulose, hydroxypropylmethylcellulose and ethylcellulose, high permeable

poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride and low permeable
poly (ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride.

21. The formulation of claim 1 wherein the ratio between the water high permeable and the water low permeable polymer in the coating is from 10:1 to 1:5.

22. The formulation of claim 1 wherein the ratio between the water high permeable and the water low permeable polymers in the coating is from 3:1 to 1:3

23. The formulation of claim 1 wherein the coating represents 1 to 15 wt.% of the total weight of the formulation.

24. The formulation of claim 1 wherein the coating further comprises a plasticizer selected from the group consisting of acetyl tributyl citrate, acetyl triethyl citrate, acetylated fatty acid glycerides, castor oil, dibutyl phthalate, diethyl phthalate, diethyl sebacate, dibutyl sebacate, dimethyl phthalate, glycerol, glycerol monostearate, glyceryl triacetate, polyethylene glycols, polyoxyethylene/polyoxypropylene copolymers, propylene glycol, tributyl citrate, triethyl citrate.

25. The formulation of claim 24 wherein the plasticizer is triethyl citrate.

26. A process for the preparation of a solid controlled release pharmaceutical formulation comprising the steps of:

dissolving venlafaxine and polyvinylpyrrolidone in an organic solvent,

applying the resulting solution onto low viscosity polymer,

homogeneously mixing the obtained granulate with a high viscosity polymer, and

compressing the granulate to obtain a core which is then coated with a polymeric coating comprising a water high permeable polymer and a water low permeable polymer.

27. The process of claim 26 wherein venlafaxine in amorphous or in polymorphous form is dissolved in an organic solvent.

28. The process of claims 26 or 27 wherein the organic solvent is selected from the group consisting of ethanol, methanol, isopropyl alcohol, n-butyl alcohol, acetone, diethyl ether, ethyl acetate, isopropyl acetate, methyl acetate, dichloromethane, chloroform and mixtures thereof.

29. The process of claim 26 or 28 wherein the organic solvent is ethanol.

30. The process of claim 26 wherein the film coating is applied from organic solvent or aqueous media.

31. The process of claim 26 wherein the low viscosity hydrophilic polymer and the high viscosity hydrophilic polymer in the core are selected from cellulose ethers.

32. The process of claim 26 wherein the low viscosity hydrophilic polymer and the high viscosity hydrophilic polymer in the core are selected from the group consisting of methylcellulose, ethylcellulose, hydroxyethylcellulose, propylcellulose, hydroxypropylcellulose, hydroxypropylmethylcellulose or carboxymethylcellulose.

33. The process of claim 26 wherein the low viscosity hydrophilic polymer and the high viscosity hydrophilic polymer in the core are a low viscosity hydroxypropylmethylcellulose and a high viscosity hydroxypropylmethylcellulose.

34. The process of claim 26 wherein the water high permeable polymer in the coating is selected from the group consisting of

methylcellulose, hydroxypropylcellulose,
hydroxypropylmethylcellulose, hydroxyethylcellulose,
methacrylate aminoester copolymer, high permeable poly
(ethylacrylate, methylmethacrylate)
trimethylammoniummethylmethacrylate chloride.

35. The process of claim 26 wherein the water high permeable polymer in the coating is selected from the group consisting of hydroxypropylcellulose, hydroxypropylmethylcellulose and high permeable poly (ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride.

36. The process of claim 26 wherein the water low permeable polymer in the coating is selected from ethylcellulose, cellulose acetate phthalate, methacrylic acid copolymers, polyvinyl acetate phthalate, cellulose acetate trimellitate, hydroxypropylmethylcellulose phthalate and low permeable poly (ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride.

37. The process of claim 26 wherein the water low permeable polymer in the coating is selected from ethylcellulose, hydroxypropylmethylcellulose phthalate and low permeable poly (ethylacrylate, methylmethacrylate) trimethylammoniummethylmethacrylate chloride.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 02/00001

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61K31/137 A61K9/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

PAJ, EPO-Internal, WPI Data, MEDLINE, BIOSIS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1 027 887 A (PFIZER PROD INC) 16 August 2000 (2000-08-16) * '0076!-'0079!; p.5, 1.12; claims 1-30 *	1-37
A	WO 99 22724 A (AMERICAN HOME PROD) 14 May 1999 (1999-05-14) cited in the application claims 1-44	1-37
A	WO 98 47491 A (ODIDI AMINA ;ODIDI ISA (CA)) 29 October 1998 (1998-10-29) * p.6, 1.1; claims 1-22 *	1-37
A	WO 94 27589 A (ALZA CORP) 8 December 1994 (1994-12-08) cited in the application claims 5,6	1-37
	-/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *S* document member of the same patent family

Date of the actual completion of the international search

2 October 2002

Date of mailing of the international search report

11/10/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Uiber, P

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 02/00001

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 252 786 A (WEISS AARON L ET AL) 24 February 1981 (1981-02-24) claims 1-19 -----	1-37

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/IB 02/00001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1027887	A	16-08-2000	BR 0000359 A EP 1027887 A2 JP 2000229888 A	14-08-2001 16-08-2000 22-08-2000
WO 9922724	A	14-05-1999	AU 747978 B2 AU 1300399 A BG 104397 A BR 9813179 A CA 2305242 A1 CN 1278165 T CZ 20001659 A3 EE 200000212 A EP 1028718 A2 HR 20000213 A1 JP 2001521892 T NO 20002126 A PL 341141 A1 SK 6472000 A3 TR 200001232 T2 WO 9922724 A2 US 6274171 B1 US 2001055612 A1 US 2002025339 A1 ZA 9810081 A	30-05-2002 24-05-1999 28-02-2001 22-08-2000 14-05-1999 27-12-2000 17-10-2001 16-04-2001 23-08-2000 31-12-2000 13-11-2001 04-05-2000 26-03-2001 07-11-2000 21-12-2000 14-05-1999 14-08-2001 27-12-2001 28-02-2002 04-05-2000
WO 9847491	A	29-10-1998	AU 6817098 A CA 2216215 A1 WO 9847491 A2	13-11-1998 05-10-1998 29-10-1998
WO 9427589	A	08-12-1994	US 6440457 B1 AU 677080 B2 AU 7048294 A CA 2157186 A1 EP 0700289 A1 FI 955681 A JP 8510755 T NO 954694 A NZ 267841 A WO 9427589 A2 ZA 9403743 A	27-08-2002 10-04-1997 20-12-1994 08-12-1994 13-03-1996 24-11-1995 12-11-1996 24-11-1995 26-11-1996 08-12-1994 24-01-1995
US 4252786	A	24-02-1981	NONE	

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 July 2003 (10.07.2003)

PCT

(10) International Publication Number
WO 2003/055475 A1

(51) International Patent Classification⁷: **A61K 31/137**

GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(21) International Application Number:
PCT/IB2002/000001

(22) International Filing Date: 3 January 2002 (03.01.2002)

(25) Filing Language: English

(26) Publication Language: English

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): LEK PHARMACEUTICAL AND CHEMICAL COMPANY D.D. [SI/SI]; Legal Affairs and Industrial Property, Industrial Property Department, Verovskova 57, 1526 Ljubljana (SI).

Published:
— with international search report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): JANEZ, Kerc [SI/SI]; Trebinjska 7, 1000 Ljubljana (SI). VLASTA, Humar [SI/SI]; Godic 63, 1242 Stahovica (SI).

(48) Date of publication of this corrected version:
29 July 2004

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,

(15) Information about Correction:
see PCT Gazette No. 31/2004 of 29 July 2004, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONTROLLED RELEASE PHARMACEUTICAL FORMULATION CONTAINING VENLAFAXINE

(57) Abstract: A solid controlled release pharmaceutical formulation for once daily administration comprises a core comprising venlafaxine, polyvinylpyrrolidone, a low viscosity hydrophilic polymer and a high viscosity hydrophilic polymer, and a polymeric coating comprising a water high permeable polymer, and a water low permeable polymer. The invention further relates to a process for the preparation of a solid controlled release pharmaceutical formulation comprising the steps of dissolving venlafaxine and polyvinylpyrrolidone in an organic solvent, applying the resulting solution onto low viscosity polymer, homogeneously mixing the obtained granulate with a high viscosity polymer, and compressing the granulate to obtain a core which is then coated with a polymeric coating comprising a water high permeable polymer and a water low permeable polymer.

WO 2003/055475 A1

THIS PAGE BLANK (USPTO)

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 July 2003 (10.07.2003)

PCT

(10) International Publication Number
WO 2003/055475 A1

(51) International Patent Classification⁷: **A61K 31/137**

LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(21) International Application Number:
PCT/IB2002/000001

(22) International Filing Date: 3 January 2002 (03.01.2002)

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): LEK PHARMACEUTICAL AND CHEMICAL COMPANY D.D. [SI/SI]; Legal Affairs and Industrial Property, Industrial Property Department, Verovskova 57, 1526 Ljubljana (SI).

Published:
— *with international search report*

(48) Date of publication of this corrected version:
26 May 2005

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): KERC, Janez [SI/SI]; Trebinjska 7, 1000 Ljubljana (SI). HUMAR, Vlasta [SI/SI]; Godic 63, 1242 Stahovica (SI).

(15) Information about Corrections:
see PCT Gazette No. 21/2005 of 26 May 2005, Section II
Previous Correction:
see PCT Gazette No. 31/2004 of 29 July 2004, Section II

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONTROLLED RELEASE PHARMACEUTICAL FORMULATION CONTAINING VENLAFAXINE

(57) Abstract: A solid controlled release pharmaceutical formulation for once daily administration comprises a core comprising venlafaxine, polyvinylpyrrolidone, a low viscosity hydrophilic polymer and a high viscosity hydrophilic polymer, and a polymeric coating comprising a water high permeable polymer, and a water low permeable polymer. The invention further relates to a process for the preparation of a solid controlled release pharmaceutical formulation comprising the steps of dissolving venlafaxine and polyvinylpyrrolidone in an organic solvent, applying the resulting solution onto low viscosity polymer, homogeneously mixing the obtained granulate with a high viscosity polymer, and compressing the granulate to obtain a core which is then coated with a polymeric coating comprising a water high permeable polymer and a water low permeable polymer.

THIS PAGE BLANK (USPTO)
